Mr. Virgil Miller **Newmar Corporation** P.O. Box 30 Nappanee, Indiana 46550

> Re: Significant Source Modification No: 039-11239-00157

Dear Mr. Miller:

Newmar Corporation applied for a Part 70 operating permit on December 13, 1996, for a motor home and travel trailer manufacturing operation. An application to modify the source was received on August 12, 1999. Pursuant to 326 IAC 2-7-10.5 the following emission units are approved for construction at the source:

(a) One (1) undercoating booth, identified as EU-08, using an airless spray application system, coating a maximum of 2.5 wood and metal chassis per hour, exhausting to the general ventilation.

The proposed Significant Source Modification approval will be incorporated into the pending Part 70 permit application pursuant to 326 IAC 2-7-10.5(I)(3). If there are no changes to the proposed construction of the emission units, the source may begin operating on the date that IDEM receives an affidavit of construction pursuant to 326 IAC 2-7-10.5(h). If there are any changes to the proposed construction the source can not operate until an Operation Permit Validation Letter is issued.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter contact Trish Earls, c/o OAM, 100 North Senate Avenue, P.O. Box 6015, Indianapolis, Indiana, 46206-6015, or call (973) 575-2555, ext. 3219, or call (800) 451-6027, press 0 and ask for extension 3-6878.

Sincerely,

Paul Dubenetzky, Chief Permits Branch Office of Air Management

Attachments TE/EVP

File - Elkhart County CC: U.S. EPA, Region V

Elkhart County Health Department

Air Compliance Section Inspector Greg Wingstrom

Compliance Data Section - Karen Nowak Administrative and Development - Janet Mobley Technical Support and Modeling - Michelle Boner

PART 70 SIGNIFICANT SOURCE MODIFICATION OFFICE OF AIR MANAGEMENT

Newmar Corporation 355 North Delaware Nappanee, Indiana 46550

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this approval.

This approval is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Source Modification No.: 039-11239-00157	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

TABLE OF CONTENTS

Α	ടവ	UR	CE	SU	MM	ARY
$\overline{}$	$\overline{}$		\smile	-		\neg ı

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
- A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

B GENERAL CONSTRUCTION CONDITIONS

- B.1 Permit No Defense [IC 13]
- B.2 Definitions [326 IAC 2-7-1]
- B.3 Effective Date of the Permit [IC13-15-5-3]
- B.4 Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]
- B.5 Significant Source Modification [326 IAC 2-7-10.5(h)]

C GENERAL OPERATION CONDITIONS

- C.1 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]
- C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
- C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]
- C.4 Opacity [326 IAC 5-1]
- C.5 Operation of Equipment [326 IAC 2-7-6(6)]
- C.6 Performance Testing [326 IAC 3-6][326 IAC 2-1.1-11]
- C.7 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.8 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
- C.9 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]
- C.10 General Record Keeping Requirements [326 IAC 2-7-5(3)]
- C.11 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

D.1 FACILITY OPERATION CONDITIONS - One (1) Undercoating Spray Booth

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Particulate Matter (PM) [326 IAC 6-3-2(c)]
- D.1.2 Volatile Organic Compounds (VOC) [326 IAC 8-2-9]

Compliance Determination Requirements

- D.1.3 Testing Requirements [326 IAC 2-7-6(1),(6)][326 IAC 2-1.1-11]
- D.1.4 Volatile Organic Compounds (VOC)

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.5 Record Keeping Requirements

Certification

SECTION A

SOURCE SUMMARY

This approval is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM). The information describing the emission units contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this approval pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates a stationary motor home and travel trailer manufacturing operation.

Responsible Official: Virgil Miller

Source Address: 355 North Delaware, Nappanee, Indiana 46550

Mailing Address: P.O. Box 30, Nappanee, Indiana 46550

Phone Number: 219-773-7791 SIC Code: 3716, 3792 County Location: Elkhart

County Status: Attainment for all criteria pollutants

Source Status: Part 70 Permit Program

Minor Source, under PSD Rules;

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source is approved to construct and operate the following emission units and pollution control devices:

(a) One (1) undercoating booth, identified as EU-08, using an airless spray application system, coating a maximum of 2.5 wood and metal chassis per hour, exhausting to the general ventilation.

A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 Applicability).

SECTION B GENERAL CONSTRUCTION CONDITIONS

B.1 Permit No Defense [IC 13]

This approval to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions [326 IAC 2-7-1]

Terms in this approval shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.

B.4 Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

B.5 Significant Source Modification [326 IAC 2-7-10.5(h)]

This document shall also become the approval to operate pursuant to 326 IAC 2-7-10.5(h) when, prior to start of operation, the following requirements are met:

- (a) The attached affidavit of construction shall be submitted to the Office of Air Management (OAM), Permit Administration & Development Section, verifying that the emission units were constructed as proposed in the application. The emissions units covered in the Significant Source Modification approval may begin operating on the date the affidavit of construction is postmarked or hand delivered to IDEM if constructed as proposed.
- (b) If actual construction of the emissions units differs from the construction proposed in the application, the source may not begin operation until the source modification has been revised pursuant to 326 IAC 2-7-11 or 326 IAC 2-7-12 and an Operation Permit Validation Letter is issued.
- (c) If construction is completed in phases; i.e., the entire construction is not done continuously, a separate affidavit must be submitted for each phase of construction. Any permit conditions associated with operation start up dates such as stack testing for New Source Performance Standards (NSPS) shall be applicable to each individual phase.
- (d) The Permittee shall receive an Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section and attach it to this document.

However, in the event that the Title V application is being processed at the same time as this application, the following additional procedures shall be followed for obtaining the right to operate:

- (1) If the Title V draft permit has not gone on public notice, then the change/addition covered by the Significant Source Modification will be included in the Title V draft.
- (2) If the Title V permit has gone thru final EPA proposal and would be issued ahead of the Significant Source Modification, the Significant Source Modification will go thru a concurrent 45 day EPA review. Then the Significant Source Modification will be incorporated into the final Title V permit at the time of issuance.

Page 5 of 13 Source Modification No. 039-11239-00157

Newmar Corporation Nappanee, Indiana Permit Reviewer: TE/EVP

(3) If the Title V permit has not gone thru final EPA review and would be issued after the Significant Source Modification is issued, then the Modification would be added to the proposed Title V permit, and the Title V permit will issued after EPA review.

Newmar Corporation
Page 6 of 13
Nappanee, Indiana
Source Modification No. 039-11239-00157
Permit Reviewer: TE/EVP

SECTION C

GENERAL OPERATION CONDITIONS

C.1 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this approval or required by an applicable requirement, any application form, report, or compliance certification submitted under this approval shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this approval, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this approval, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions:
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management Compliance Branch, Office of Air Management 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that failure to implement the Preventive Maintenance Plan does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM. IDEM, OAM, may require the Permittee to revise its Preventive Maintenance Plan whenever lack of proper maintenance causes or contributes to any violation.

C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this approval.
- (b) Any application requesting an amendment or modification of this approval shall be submitted to:

Page 7 of 13 Source Modification No. 039-11239-00157

Newmar Corporation Nappanee, Indiana Permit Reviewer: TE/EVP

> Indiana Department of Environmental Management Permits Branch, Office of Air Management 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

C.4 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this approval:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

C.5 Operation of Equipment [326 IAC 2-7-6(6)]

Except as otherwise provided in this approval, all air pollution control equipment listed in this approval and used to comply with an applicable requirement shall be operated at all times that the emission unit vented to the control equipment is in operation.

Testing Requirements [326 IAC 2-7-6(1)]

C.6 Performance Testing [326 IAC 3-6][326 IAC 2-1.1-11]

(a) Compliance testing on new emission units shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this approval, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this approval, shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Management 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

Page 8 of 13 Source Modification No. 039-11239-00157

Newmar Corporation Nappanee, Indiana Permit Reviewer: TE/EVP

(b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAM, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.7 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this approval. All monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of approval issuance. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management Compliance Branch, Office of Air Management 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.8 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]
 - (a) When the results of a stack test performed in conformance with Section C Performance Testing, of this approval exceed the level specified in any condition of this
 approval, the Permittee shall take appropriate corrective actions. The Permittee shall
 submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of
 receipt of the test results. The Permittee shall take appropriate action to minimize
 emissions from the affected facility while the corrective actions are being implemented.
 IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions
 taken are deficient. The Permittee shall submit a description of additional corrective
 actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency.
 IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant
 stack tests.
 - (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate approval conditions may be grounds for immediate revocation of the approval to operate the affected facility.

Page 9 of 13 Source Modification No. 039-11239-00157

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.9 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]

- (a) With the exception of performance tests conducted in accordance with Section C-Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this approval shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this approval is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this approval.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.10 General Record Keeping Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-6]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAM, representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Records of required monitoring information shall include, where applicable:
 - (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and

- (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this approval;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that failure to implement the Preventive Maintenance Plan did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C Compliance Monitoring Plan Failure to take Response Steps, of this approval, and whether a deviation from an approval condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of approval issuance.

C.11 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

(a) The reports required by conditions in Section D of this approval shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Management 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

- (b) Unless otherwise specified in this approval, any notice, report, or other submission required by this approval shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) Unless otherwise specified in this approval, any semi-annual report shall be submitted within thirty (30) days of the end of the reporting period. The report does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) The first report shall cover the period commencing on the date of issuance of this approval and ending on the last day of the reporting period.

SECTION D.1

FACILITY OPERATION CONDITIONS

Page 11 of 13

Facility Description [326 IAC 2-7-5(15)]

One (1) undercoating booth, identified as EU-08, using an airless spray application system, (a) coating a maximum of 2.5 wood and metal chassis per hour, exhausting to the general ventilation.

Emission Limitations and Standards [326 IAC 2-7-5(1)]

Particulate Matter (PM) [326 IAC 6-3-2(c)] D.1.1

The PM from the undercoating booth shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 P^{0.67}$ where E = rate of emission in pounds per hour; and P = process weight rate in tons per hour

Volatile Organic Compounds (VOC) [326 IAC 8-2-9] D.1.2

- Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coatings applied to metal parts or products in the undercoating booth shall be limited to 3.5 pounds of VOC per gallon of coating less water delivered to the applicator, for air dried or forced warm air dried coatings.
- (b) Solvent sprayed from the application equipment during clean up or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

Compliance Determination Requirements

Testing Requirements [326 IAC 2-7-6(1),(6)][326 IAC 2-1.1-11] D.1.3

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM or VOC limits specified in Conditions D.1.1 and D.1.2 shall be determined by a performance test conducted in accordance with Section C -Performance Testing.

D.1.4 Volatile Organic Compounds (VOC)

Compliance with the VOC content limitation contained in Condition D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAM, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

Record Keeping Requirements D.1.5

To document compliance with Condition D.1.2, the Permittee shall maintain records in (a) accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.2.

Page 12 of 13 Source Modification No. 039-11239-00157

- (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
- (2) A log of the dates of use;
- (3) The cleanup solvent usage for each month;
- (4) The total VOC usage for each month; and
- (5) The weight of VOCs emitted for each compliance period.
- (b) All records shall be maintained in accordance with Section C General Record Keeping Requirements, of this permit.

Page 13 of 13 Source Modification No. 039-11239-00157

Newmar Corporation Nappanee, Indiana Permit Reviewer: TE/EVP

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR MANAGEMENT COMPLIANCE DATA SECTION

PART 70 SOURCE MODIFICATION CERTIFICATION

Source Name: Newmar Corporation

Source Address: 355 North Delaware, Nappanee, Indiana 46550

Mailing Address: P.O. Box 30. Nappanee. Indiana 46550

Source Modification No.: 039-11239-00157	
This certification shall be included when submitting monitoring, test or other documents as required by this approva	• .
Please check what document is being certified:	
9 Test Result (specify)	
9 Report (specify)	
9 Notification (specify)	
9 Other (specify)	
I certify that, based on information and belief formed after reasonable incinformation in the document are true, accurate, and complete.	quiry, the statements and
Signature:	
Printed Name:	
Title/Position:	
Date:	

Indiana Department of Environmental Management Office of Air Management

Technical Support Document (TSD) for a Part 70 Significant Source Modification.

Source Background and Description

Source Name: Newmar Corporation

Source Location: 355 North Delaware, Nappanee, Indiana 46550

County: Elkhart
SIC Code: 3716, 3792
Operation Permit No.: T039-7571-00157
Operation Permit Issuance Date: Still pending
Source Modification No.: 039-11239-00157
Permit Reviewer: Trish Earls/EVP

The Office of Air Management (OAM) has reviewed a modification application from Newmar Corporation relating to the construction of the following emission units and pollution control devices:

(a) One (1) undercoating booth, identified as EU-08, using an airless spray application system, coating a maximum of 2.5 wood and metal chassis per hour, exhausting to the general ventilation.

History

On August 12, 1999, Newmar Corporation submitted an application to the OAM requesting to add an additional undercoating spray booth to their existing plant. Newmar Corporation has applied for a Part 70 permit for the existing source which was received on December 13, 1996. The Title V permit application (T-039-7571-00157) is currently being reviewed by IDEM.

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the Part 70 Significant Source Modification be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on August 12, 1999.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (1 page).

Potential To Emit of Modification

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA."

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	42.51
PM-10	42.51
SO ₂	0.0
VOC	3.91
CO	0.0
NO _x	0.0

There are no HAPs emitted from this facility.

Justification for Modification

The Part 70 Operating permit is being modified through a Part 70 Significant Source Modification. This modification is being performed pursuant to 326 IAC 2-7-10.5(g).

County Attainment Status

The source is located in Elkhart County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO_2	attainment
Ozone	maintenance
СО	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NOx) are precursors for the formation of ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Elkhart County has been designated as maintenance for ozone as of 11/94. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.
- (b) Elkhart County has been classified as attainment or unclassifiable for all other regulated pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Existing Source PSD or Emission Offset Definition (emissions after controls, based upon 8760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/year)
PM	N/A
PM-10	4.73
SO ₂	0.0
VOC	78.75
со	0.0
NOx	0.0

- (a) This existing source is not a major stationary source because no attainment regulated pollutant is emitted at a rate of 250 tons per year or more, and it is not one of the 28 listed source categories.
- (b) These emissions are based upon the 1998 Emission Statement for this source.

Potential to Emit of Modification After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units after controls. The control equipment is considered federally enforceable only after issuance of this Part 70 source modification.

	Potential to Emit (tons/year)									
Process/facility	PM	PM PM-10 SO ₂ VOC CO NO _X								
Undercoating Booth	42.51	42.51	0.0	3.91	0.0	0.0	0.0			
PSD Threshold Level	250	250	250	250	250	250	N/A			

This modification to an existing minor stationary source is not major because the emission increase is less than the PSD significant levels. Therefore, pursuant to 326 IAC 2-2, and 40 CFR 52.21, the PSD requirements do not apply.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this proposed modification.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this proposed modification.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

326 IAC 6-4 (Fugitive Dust Emissions)

The undercoating booth shall comply with the fugitive dust limitations outlined in 326 IAC 6-4 (Fugitive Dust Emissions). Pursuant to 326 IAC 6-4, no fugitive dust emissions shall be visible crossing the boundary or property line of the source. Observances of visible emissions crossing property lines may be refuted by factual data expressed in 326 IAC 6-4-2(1), (2) or (3).

326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from the undercoating booth shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 P^{0.67}$ where E = rate of emission in pounds per hour and P = process weight rate in tons per hour

326 IAC 8-1-6 (New Facilities, General Reduction Requirements)

The undercoating booth is not subject to the requirements of this rule because potential VOC emissions are less than 25 tons per year.

326 IAC 8-2-9 (Miscellaneous Metal Coating)

The wood and metal chassis coating operation at the undercoating booth is not subject to the requirements of this rule, because actual VOC usages for the chassis coating operation are less than fifteen (15) pounds per day.

326 IAC 8-2-12 (Wood Furniture and Cabinet Coating)

The wood and metal chassis coating operation at the undercoating booth is not subject to the requirements of this rule, because the chassis for motor home and travel trailer is not wood furniture.

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Page 5 of 5 Source Mod #:039-11239-00157

Newmar Corporation Nappanee, Indiana Permit Reviewer: TE/EVP

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

There are no compliance monitoring requirements applicable to this modification.

Conclusion

The construction of this proposed modification shall be subject to the conditions of the attached proposed Part 70 Significant Source Modification No. 039-11239-00157.

Indiana Department of Environmental Management Office of Air Management

Addendum to the Technical Support Document for a Part 70 Significant Source Modification

Source Name: Newmar Corporation

Source Location: 355 North Delaware, Nappanee, Indiana 46550

County: Elkhart

Source Modification No.: 039-11239-00157 SIC Code: 3716, 3792 Permit Reviewer: Trish Earls/EVP

On October 29, 1999, the Office of Air Management (OAM) had a notice published in The Elkhart Truth, Elkhart, Indiana, stating that Newmar Corporation had applied for a Significant Source Modification to construct one (1) undercoating spray booth at their existing motor home and travel trailer manufacturing operation. The notice also stated that OAM proposed to issue a permit for this installation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

On November 19, 1999, Newmar Corporation submitted comments on the proposed permit. The summary of the comments and corresponding responses is as follows:

Comment #1

Newmar Corporation requests that the requirement for a Preventive Maintenance Plan in condition D.1.3, be removed on the basis that this process does not utilize any control devices, thus not requiring a PMP.

Response #1

Since the undercoating booth does not have any control devices, and actual PM and VOC emissions are each less than 25 tons per year, a Preventive Maintenance Plan is not required. Therefore, condition D.1.3 has been deleted from the permit and all subsequent conditions have been re-numbered.

Comment #2

Newmar Corporation requests that the daily record keeping requirements in condition D.1.7 be amended. This requirement is onerous and would require excessive amounts of record keeping for a very minute source of VOCs. Newmar believes that a material safety data sheet documenting that the VOC content is below 3.5 pounds per gallon would better serve the requirements of 326 IAC 8-2-9.

Newmar Corporation Nappanee, Indiana

Permit Reviewer: TE/EVP

Response #2

To change the record keeping requirements from daily to monthly, the undercoating booth must comply with the requirements of 326 IAC 8-2-9. This rule limits the VOC content of air dried or forced warm air dried coatings used to less than or equal to 3.5 pounds of VOC per gallon of coating, excluding water. Since all of the coatings used in the undercoating booth are in compliance with this limit, the source has chosen to be subject to the requirements of this rule. Therefore, the record keeping requirements in condition D.1.7 (now re-numbered as D.1.5) have been changed from daily to monthly and the requirement to keep a record of the volume weighted average VOC content has been deleted, since all of the coatings used are in compliance with the VOC content limit. Also, condition D.1.2 has been revised to include the requirements of 326 IAC 8-2-9 and condition D.1.5 (now re-numbered as D.1.4) has been revised to refer to a VOC content limit instead of a usage limit. The revised conditions read as follows:

Page 2 of 3

Source Mod. No.: 039-11239-00157

D.1.2 Volatile Organic Compounds (VOC) [326 IAC 8-2-9]

The actual usage of VOC, including coatings, dilution solvents, and cleaning solvents, in the undercoating booth is less than fifteen (15) pounds per day. Therefore, the requirements of 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations) will not apply. Any change or modification which may increase VOC usages in the undercoating booth to more than 15 pounds per day shall require approval from IDEM, OAM prior to making the change.

- (a) Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coatings applied to metal parts or products in the undercoating booth shall be limited to 3.5 pounds of VOC per gallon of coating less water delivered to the applicator, for air dried or forced warm air dried coatings.
- (b) Solvent sprayed from the application equipment during clean up or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

D.1.54 Volatile Organic Compounds (VOC)

Compliance with the VOC usage content limitation contained in Condition D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAM, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.**75** Record Keeping Requirements

- To document compliance with Condition D.1.2, the Permittee shall maintain records in accordance with (1) through (6)(5) below. Records maintained for (1) through (6)(5) shall be taken daily monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.2.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - The volume weighted VOC content of the coatings used for each day;

Newmar Corporation Page 3 of 3
Nappanee, Indiana Source Mod. No.: 039-11239-00157
Permit Reviewer: TE/EVP

- (4)(3) The cleanup solvent usage for each day month;
- (5)(4) The total VOC usage for each day month; and
- (6)(5) The weight of VOCs emitted for each compliance period.
- (b) All records shall be maintained in accordance with Section C General Record Keeping Requirements, of this permit.

The State Rule Applicability section of the TSD, discussing the applicability of 326 IAC 8-2-9, is revised to read as follows:

326 IAC 8-2-9 (Miscellaneous Metal Coating)

The wood and metal chassis coating operation, which uses air dried coatings, at the undercoating booth is not subject to the requirements of this rule, because actual VOC usages for the chassis coating operation are less than fifteen (15) pounds per day. Pursuant to this rule, the volatile organic compound (VOC) content of coatings applied to metal parts or products in the undercoating booth shall be limited to 3.5 pounds of VOC per gallon of coating less water delivered to the applicator, for air dried or forced warm air dried coatings.

Solvent sprayed from the application equipment during clean up or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

The source shall comply with this rule by using coatings in the undercoating booth with a VOC content less than or equal to 3.5 pounds of VOC per gallon of coating less water.

Page 1 of 1 TSD App A

Appendix A: Emissions Calculations VOC and Particulate From Surface Coating Operations

Company Name: Newmar Corporation

Address City IN Zip: 355 North Delaware, Nappanee, Indiana 46550

Significant Source Mod. No.: 039-11239 **Plt ID:** 039-00157

Reviewer: Trish Earls/EVP

Date: August 12, 1999

Material	Density (Lb/Gal)	Weight % Volatile (H20 & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)		Transfer Efficiency
Undercoating Booth																
Undercoating	8.7	50.00%	48.9%	1.15%	55.0%	50.00%	3.57000	2.500	0.22	0.10	0.89	21.43	3.91	42.51	0.20	75%

State Potential Emissions Add worst case coating to all solvents 0.89 21.43 3.91 42.51

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used